



- 1

Polyurethane (PUR) surface treatment
- 2

Transparent wear layer
- 3

Printed décor layer
- 4

Backing Layer



Product Specification

Overview		
Thickness	5.0mm	
Wear Layer	0.30mm (12 mil)	
Size	7 1/4" x 48"	
Surface treatment	PUR coating	
Edges	Micro-bevel	
Packaging	10 pcs, 24.17 sqft/box	
Warranty*	Light Commercoal	10 years
	Residential	15 years

ASTM Standards - Safety and Performance			
	Standard	Requirement	Result
Squareness	ASTM F2055	≤0.01" (0.25mm)	Pass
Residual Indentation	ASTM F1914	≤8%	Pass
Dimensional Stability	ASTM F2199	≤0.02" / linear foot (0.16%)	Pass
Heavy Metals	ASTM F963	Refer to Standard	ND
Chemical Resistance	ASTM F925	No more than "Slight change"	Pass
Resistance to Heat and Light	ASTM F1514 & F1515	ΔE≤ 8.0	Pass
Burning Mode (Critical Radiant Flux)	ASTM E648	Class 1 (≥0.45 W/cm²)	Pass
Burning Mode (Smoke Density)	ASTM E662	< 450	Pass
Static Load	ASTM F970	< 0.005", 250 lbs load	Pass
Castor Chair	ISO 4918	Slight change in apprearance No delaminaton	Pass
VOC Emission Criteria	CHPS 01350		FloorScore Certificated

* Subject To Terms